

LED DOT MATRIX
BL-M23X881
Features:

- 60.20mm (2.3") Φ5.0 dot matrix LED display.
- Low current operation.
- Excellent character appearance.
- Easy mounting on P.C. Boards or sockets.
- I.C. Compatible.
- ROHS Compliance.


Super Bright
Electrical-optical characteristics: (Ta=25°C) (Test Condition: IF=20mA)

Part No		Chip			VF Unit:V		Iv
Row Cathode	Column Anode	Row Anode	Column Cathode	Emitted Color	Material	λ _p (nm)	TYP.(mcd)
BL-M23A881S-XX		BL-M23B881S-XX		Hi Red	GaAlAs/GaAs,SH	660	280
BL-M23A881D-XX		BL-M23B881D-XX		Super Red	GaAlAs/GaAs,DH	660	310
BL-M23A881UR-XX		BL-M23B881UR-XX		Ultra Red	GaAlAs/GaAs,DDH	660	450
BL-M23A881E-XX		BL-M23B881E-XX		Orange	GaAsP/GaP	635	220
BL-M23A881Y-XX		BL-M23B881Y-XX		Yellow	GaAsP/GaP	585	220
BL-M23A881G-XX		BL-M23B881G-XX		Green	GaP/GaP	570	250

Ultra Bright
Electrical-optical characteristics: (Ta=25°C) (Test Condition: IF=20mA)

Part No		Chip			VF Unit:V		Iv
Row Cathode	Column Anode	Row Anode	Column Cathode	Emitted Color	Material	λ _p (nm)	TYP.(mcd)
BL-M23A881UHR-XX		BL-M23B881UHR-XX		Ultra Red	AlGaInP	645	450
BL-M23A881UE-XX		BL-M23B881UE-XX		Ultra Orange	AlGaInP	630	255
BL-M23A881YO-XX		BL-M23B881YO-XX		Ultra Amber	AlGaInP	619	255
BL-M23A881UY-XX		BL-M23B881UY-XX		Ultra Yellow	AlGaInP	590	255
BL-M23A881UG-XX		BL-M23B881UG-XX		Ultra Green	AlGaInP	574	380
BL-M23A881PG-XX		BL-M23B881PG-XX		Ultra Pure Green	InGaN	525	560
BL-M23A881B-XX		BL-M23B881B-XX		Ultra Blue	InGaN	470	270
BL-M23A881W-XX		BL-M23B881W-XX		Ultra White	InGaN	/	350

--XX: Surface / Lens color:

Number	0	1	2	3	4	5
Ref Surface Color	White	Black	Gray	Red	Green	
Epoxy Color	Water clear	White diffused	Red Diffused	Green Diffused	Yellow Diffused	

LED DOT MATRIX
BL-M23X881
Absolute maximum ratings (Ta=25°C)

Parameter	S	D	UR	E	Y	G	Unit
Forward Current I_F	25	25	25	25	25	30	mA
Power Dissipation P_d	60	60	60	60	60	65	mW
Reverse Voltage V_R	5	5	5	5	5	5	V
Peak Forward Current I_{PF} (Duty 1/10 @1KHZ)	150	150	150	150	150	150	mA
Operation Temperature T_{OPR}	-40 to +80						°C
Storage Temperature T_{STG}	-40 to +85						°C
Lead Soldering Temperature T_{SOL}	Max.260±5°C for 3 sec Max. (1.6mm from the base of the epoxy bulb)						°C

■ Absolute maximum ratings (Ta=25°C)


Parameter	UHR	UE	YO	UY	UG	PG	B	W	Unit
Forward Current I_F	30	30	30	30	30	30	30	30	mA
Power Dissipation P_d	75	65	65	65	75	110	120	120	mW
Reverse Voltage V_R	5	5	5	5	5	5	5	5	V
Peak Forward Current I_{PF} (Duty 1/10 @1KHZ)	150	150	150	150	150	150	100	100	mA
Operation Temperature T_{OPR}	-40 to +80								°C
Storage Temperature T_{STG}	-40 to +85								°C
Lead Soldering Temperature T_{SOL}	Max.260±5°C for 3 sec Max. (1.6mm from the base of the epoxy bulb)								°C

LED DOT MATRIX


BL-M23X881

■ Package configuration & Internal circuit diagram


BL-M23X881 Series



BL-M23A881



BL-M23B881




Notes:

1. All dimensions are in millimeters (inches)
2. Tolerance is $\pm 0.25(0.01)$ unless otherwise noted.
3. Specifications are subject to change without notice.







LED DOT MATRIX

BL-M23X881

Typical electrical-optical characteristics curves:



- | | |
|---|--------------------------------------|
| (1) - GaAsP/GaAs 655nm/Red | (9) - GaAlAs 880nm |
| (2) - GaP 570nm/Yellow Green | (10) - GaAs/GaAs & GaAlAs/GaAs 940nm |
| (3) - GaAsP/GaP 585nm/Yellow | (A) - GaN/SiC 430nm/Blue |
| (4) - GaAsP/GaP 635nm/Orange & Hi-Eff Red | (B) - InGaN/SiC 470nm/Blue |
| (5) - GaP 700nm/Bright Red | (C) - InGaN/SiC 505nm/Ultra Green |
| (6) - GaAlAs/GaAs 660nm/Super Red | (D) - InGaN/SiC 525nm/Ultra Green |
| (8) - GaAsP/GaP 610nm/Super Red | |



NOTE:25°C free air temperature unless otherwise specified